



Programme of Requirements part 3g: Certificate Policy for Authenticity and Confidentiality certificates in Private Services (G1) Domain

Version 4.11
Date February 28, 2023

Publishers imprint

Version number 4.11
Contact person Policy Authority of PKIoverheid

Organization Logius

Street address

Wilhelmina van Pruisenweg 52

Postal address

Postbus 96810

2509 JE DEN HAAG

T 0900-555 4555

servicecentrum@logius.nl

Contents

1. INTRODUCTION	10
<i>1.1 Overview</i>	10
<i>1.2 Document name and identification</i>	10
1.2.1 Revisions	10
1.2.1.1 Version 4.0 to 4.1.....	10
1.2.1.2 Version 4.1 to 4.2.....	10
1.2.1.3 Version 4.2 to 4.3.....	10
1.2.1.4 Version 4.3 to 4.4.....	11
1.2.1.5 Version 4.4 to 4.5.....	11
1.2.1.6 Version 4.5 to 4.6.....	11
1.2.1.7 Version 4.6 to 4.7.....	11
1.2.1.8 Version 4.7 to 4.8.....	12
1.2.1.9 Version 4.8 to 4.9.....	12
1.2.1.10 Version 4.9 to 4.10	12
1.2.1.11 Version 4.10 to 4.11	13
1.2.2 Relevant dates.....	13
<i>1.3 PKI participants</i>	14
1.3.1 Certification authorities	14
1.3.2 Registration authorities	14
1.3.3 Subscribers	14
1.3.4 Relying parties.....	14
1.3.5 Other participants	15
<i>1.4 Certificate usage</i>	15
1.4.1 Appropriate certificate uses	15
1.4.2 Prohibited certificate uses.....	15
<i>1.5 Policy administration</i>	15
1.5.1 Organization administering the document.....	15
1.5.2 Contact person	15
1.5.3 Person determining CPS suitability for the policy.....	15
1.5.4 CP approval procedures.....	16
<i>1.6 Definitions and acronyms</i>	16
1.6.1 Conventions	16
2. PUBLICATION AND REPOSITORY RESPONSIBILITIES	17
<i>2.1 Repositories</i>	17
<i>2.2 Publication of certification information</i>	17
<i>2.3 Time or frequency of publication</i>	17

2.4 Access controls on repositories	17
3. IDENTIFICATION AND AUTHENTICATION	18
3.1 Naming	18
3.1.1 Types of names	18
3.1.2 Need for names to be meaningful	18
3.1.3 Anonymity or pseudonymity of subscribers	18
3.1.4 Rules for interpreting various name forms	18
3.1.5 Uniqueness of names	18
3.1.6 Recognition, authentication, and role of trademarks	18
3.2 Initial identity validation	18
3.2.1 Method to prove possession of private key	18
3.2.2 Authentication of organization identity	19
3.2.3 Authentication of individual identity	19
3.2.4 Non-verified subscriber information	20
3.2.5 Validation of authority	20
3.2.6 Criteria for interoperation	21
3.3 Identification and authentication for re-key requests	21
3.3.1 Identification and authentication for routine re-key	21
3.3.2 Identification and authentication for re-key after revocation	21
3.4 Identification and authentication for revocation request	21
4. CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS	22
4.1 Certificate Application	22
4.1.1 Who can submit a certificate application	22
4.1.2 Enrollment process and responsibilities	22
4.2 Certificate application processing	22
4.2.1 Performing identification and authentication functions	22
4.2.2 Approval or rejection of certificate applications	22
4.2.3 Time to process certificate applications	22
4.3 Certificate issuance	22
4.3.1 CA actions during certificate issuance	22
4.3.2 Notification to subscriber by the CA of issuance of Certificate	22
4.4 Certificate acceptance	22
4.4.1 Conduct constituting certificate acceptance	22
4.4.2 Publication of the certificate by the CA	23
4.4.3 Notification of certificate issuance by the CA to other Entities	23
4.5 Key pair and certificate usage	23
4.5.1 Subscriber private key and certificate usage	23
4.5.2 Relying party public key and certificate usage	23
4.6 Certificate renewal	23
4.6.1 Circumstance for certificate renewal	23
4.6.2 Who may request renewal	23
4.6.3 Processing certificate renewal requests	23

4.6.4 Notification of new certificate issuance to subscriber	23
4.6.5 Conduct constituting acceptance of a renewal certificate	23
4.6.6 Publication of the renewal certificate by the CA	23
4.6.7 Notification of certificate issuance by the CA to other entities	23
<i>4.7 Certificate re-key</i>	<i>23</i>
4.7.1 Circumstance for certificate re-key	23
4.7.2 Who may request certification of a new public key	23
4.7.3 Processing certificate re-keying requests	24
4.7.4 Notification of new certificate issuance to subscriber	24
4.7.5 Conduct constituting acceptance of a re-keyed certificate	24
4.7.6 Publication of the re-keyed certificate by the CA	24
4.7.7 Notification of certificate issuance by the CA to other entities	24
<i>4.8 Certificate modification</i>	<i>24</i>
4.8.1 Circumstance for certificate modification	24
4.8.2 Who may request certificate modification	24
4.8.3 Processing certificate modification requests	24
4.8.4 Notification of new certificate issuance to subscriber	24
4.8.5 Conduct constituting acceptance of modified certificate	24
4.8.6 Publication of the modified certificate by the CA	24
4.8.7 Notification of certificate issuance by the CA to other entities	24
<i>4.9 Certificate revocation and suspension</i>	<i>24</i>
4.9.1 Circumstances for revocation	24
4.9.2 Who can request revocation.....	25
4.9.3 Procedure for revocation request	25
4.9.4 Revocation request grace period.....	26
4.9.5 Time within which CA must process the revocation request	26
4.9.6 Revocation checking requirement for relying parties.....	26
4.9.7 CRL issuance frequency (if applicable).....	26
4.9.8 Maximum latency for CRLs (if applicable)	26
4.9.9 On-line revocation/status checking availability	26
4.9.10 On-line revocation checking requirements.....	27
4.9.11 Other forms of revocation advertisements available.....	27
4.9.12 Special requirements related to key compromise	27
4.9.13 Circumstances for suspension	27
4.9.14 Who can request suspension	27
4.9.15 Procedure for suspension request	27
4.9.16 Limits on suspension period	27
<i>4.10 Certificate status services.....</i>	<i>28</i>
4.10.1 Operational characteristics.....	28
4.10.2 Service availability	28
4.10.3 Optional features.....	28
<i>4.11 End of subscription</i>	<i>28</i>
<i>4.12 Key escrow and recovery.....</i>	<i>28</i>
4.12.1 Key escrow and recovery policy and practices.....	28
4.12.2 Session key encapsulation and recovery policy and practices	28

5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS	29
<i>5.1 Physical controls</i>	<i>29</i>
5.1.1 Site location and construction	29
5.1.2 Physical access	29
5.1.3 Power and air conditioning.....	29
5.1.4 Water exposures	29
5.1.5 Fire prevention and protection	29
5.1.6 Media storage.....	29
5.1.7 Waste disposal.....	29
5.1.8 Off-site backup	29
<i>5.2 Procedural controls.....</i>	<i>29</i>
5.2.1 Trusted roles	29
5.2.2 Number of persons required per task	29
5.2.3 Identification and authentication for each role	29
5.2.4 Roles requiring separation of duties	29
<i>5.3 Personnel controls.....</i>	<i>30</i>
5.3.1 Qualifications, experience, and clearance requirements	30
5.3.2 Background check procedures.....	30
5.3.3 Training requirements	30
5.3.4 Retraining frequency and requirements	30
5.3.5 Job rotation frequency and sequence	30
5.3.6 Sanctions for unauthorized actions	30
5.3.7 Independent contractor requirements	30
5.3.8 Documentation supplied to personnel.....	30
<i>5.4 Audit logging procedures.....</i>	<i>30</i>
5.4.1 Types of events recorded.....	30
5.4.2 Frequency of processing log.....	31
5.4.3 Retention period for audit log.....	31
5.4.4 Protection of audit log	31
5.4.5 Audit log backup procedures	31
5.4.6 Audit collection system (internal vs. external)	31
5.4.7 Notification to event-causing subject.....	31
5.4.8 Vulnerability assessments.....	32
<i>5.5 Records archival</i>	<i>32</i>
5.5.1 Types of records archived	32
5.5.2 Retention period for archive.....	32
5.5.3 Protection of archive.....	32
5.5.4 Archive backup procedures	32
5.5.5 Requirements for time-stamping of records	32
5.5.6 Archive collection system (internal or external)	32
5.5.7 Procedures to obtain and verify archive information	32
<i>5.6 Key changeover.....</i>	<i>32</i>
<i>5.7 Compromise and disaster recovery.....</i>	<i>32</i>
5.7.1 Incident and compromise handling procedures	32
5.7.2 Computing resources, software, and_or data are corrupted.....	33

5.7.3 Entity private key compromise procedures	33
5.7.4 Business continuity capabilities after a disaster	33
5.8 CA or RA termination.....	33
6. TECHNICAL SECURITY CONTROLS.....	34
6.1 Key pair generation and installation.....	34
6.1.1 Key pair generation	34
6.1.2 Private key delivery to subscriber	35
6.1.3 Public key delivery to certificate issuer	35
6.1.4 CA public key delivery to relying parties	35
6.1.5 Key sizes.....	36
6.1.6 Public key parameters generation and quality checking	36
6.1.7 Key usage purposes (as per X.509 v3 key usage field)	36
6.2 Private Key Protection and Cryptographic Module Engineering Controls.....	36
6.2.1 Cryptographic module standards and controls	36
6.2.2 Private key (n out of m) multi-person control	36
6.2.3 Private key escrow	36
6.2.4 Private key backup	36
6.2.5 Private key archival	36
6.2.6 Private key transfer into or from a cryptographic module	37
6.2.7 Private key storage on cryptographic module	37
6.2.8 Method of activating private key.....	37
6.2.9 Method of deactivating private key	37
6.2.10 Method of destroying private key.....	37
6.2.11 Cryptographic Module Rating.....	37
6.3 Other aspects of key pair management.....	37
6.3.1 Public key archival.....	37
6.3.2 Certificate operational periods and key pair usage periods	37
6.4 Activation data	38
6.4.1 Activation data generation and installation.....	38
6.4.2 Activation data protection.....	38
6.4.3 Other aspects of activation data	38
6.5 Computer security controls.....	38
6.5.1 Specific computer security technical requirements	38
6.5.2 Computer security rating.....	38
6.6 Life cycle technical controls	39
6.6.1 System development controls	39
6.6.2 Security management controls.....	39
6.6.3 Life cycle security controls.....	39
6.7 Network security controls.....	39
6.7.1 Network security controls (duplicate)	39
6.8 Time-stamping	39
7. CERTIFICATE, CRL, AND OCSP PROFILES	40

<i>7.1 Certificate profile</i>	40
7.1.1 Version number(s).....	41
7.1.2 Certificate extensions	41
7.1.3 Algorithm object identifiers.....	41
7.1.4 Name forms	41
7.1.5 Name constraints	41
7.1.6 Certificate policy object identifier.....	41
7.1.7 Usage of Policy Constraints extension.....	41
7.1.8 Policy qualifiers syntax and semantics.....	41
7.1.9 Processing semantics for the critical Certificate Policies extension	41
<i>7.2 CRL profile</i>	41
7.2.1 Version number(s).....	41
7.2.2 CRL and CRL entry extensions.....	41
<i>7.3 OCSP profile</i>	41
7.3.1 Version number(s).....	42
7.3.2 OCSP extensions	42
8. COMPLIANCE AUDIT AND OTHER ASSESSMENTS	43
<i>8.1 Frequency or circumstances of assessment</i>	43
<i>8.2 Identity/qualifications of assessor</i>	43
<i>8.3 Assessors relationship to assessed entity</i>	43
<i>8.4 Topics covered by assessment</i>	43
<i>8.5 Actions taken as a result of deficiency</i>	43
<i>8.6 Communication of results</i>	43
9. OTHER BUSINESS AND LEGAL MATTERS	44
<i>9.1 Fees</i>	44
9.1.1 Certificate issuance or renewal fees	44
9.1.2 Certificate access fees.....	44
9.1.3 Revocation or status information access fees	44
9.1.4 Fees for other services	44
9.1.5 Refund policy	44
<i>9.2 Financial responsibility</i>	44
9.2.1 Insurance coverage	44
9.2.2 Other assets	44
9.2.3 Insurance or warranty coverage for end-entities	44
<i>9.3 Confidentiality of business information</i>	45
9.3.1 Scope of confidential information.....	45
9.3.2 Information not within the scope of confidential information.....	45
9.3.3 Responsibility to protect confidential information	45
<i>9.4 Privacy of personal information</i>	45
9.4.1 Privacy plan.....	45
9.4.2 Information treated as private	45

9.4.3 Information not deemed private	45
9.4.4 Responsibility to protect private information	45
9.4.5 Notice and consent to use private information	45
9.4.6 Disclosure pursuant to judicial or administrative process.....	45
9.4.7 Other information disclosure circumstances	45
<i>9.5 Intellectual property rights</i>	<i>45</i>
<i>9.6 Representations and warranties</i>	<i>45</i>
9.6.1 CA representations and warranties	45
9.6.2 RA representations and warranties	46
9.6.3 Subscriber representations and warranties.....	46
9.6.4 Relying party representations and warranties	46
9.6.5 Representations and warranties of other participants	46
<i>9.7 Disclaimers of warranties</i>	<i>46</i>
<i>9.8 Limitations of liability</i>	<i>46</i>
<i>9.9 Indemnities.....</i>	<i>46</i>
<i>9.10 Term and termination</i>	<i>46</i>
9.10.1 Term.....	46
9.10.2 Termination	46
9.10.3 Effect of termination and survival	47
<i>9.11 Individual notices and communications with participants</i>	<i>47</i>
<i>9.12 Amendments</i>	<i>47</i>
9.12.1 Procedure for amendment	47
9.12.2 Notification mechanism and period	47
9.12.3 Circumstances under which OID must be changed	47
<i>9.13 Dispute resolution provisions</i>	<i>47</i>
<i>9.14 Governing law.....</i>	<i>47</i>
<i>9.15 Compliance with applicable law</i>	<i>47</i>
<i>9.16 Miscellaneous provisions</i>	<i>47</i>
9.16.1 Entire agreement	47
9.16.2 Assignment	47
9.16.3 Severability	47
9.16.4 Enforcement (attorneys' fees and waiver of rights)	47
9.16.5 Force Majeure	47
<i>9.17 Other provisions.....</i>	<i>48</i>
Appendix A: Certificate Profile	49
<i>Services certificates for authenticity and confidentiality - Private Services domain</i>	<i>50</i>

1. INTRODUCTION

1.1 Overview

Refer to Programme of Requirements part 3 Basic Requirements.

1.2 Document name and identification

1.2.1 Revisions

1.2.1.1 Version 4.0 to 4.1

New

- Certification against ETSI TS 102 042 (effective date no later than 4 weeks after publication of PoR 4.1).

Modifications

None.

Editorial

- Small editorial modification to the following requirement:
 - Requirement 5.7.4-pkio86.

1.2.1.2 Version 4.1 to 4.2

New

- Requirement 7.1-pkio150 (effective date July 1, 2016).

Modifications

- Change in subjectAltName in the certificate profile (effective date directly after publication of PoR).

Editorial

None.

1.2.1.3 Version 4.2 to 4.3

New

- Addition of issuer.organizationalIdentifier in the certificate profile (effective date 1-7-2016).

Modifications

- Description with attribute CertificatePolicies (effective date 1-7-2016);
- Removal optional use KeyAgreement with Key Usage (effective date no later than 4 weeks after publication of PoR 4.3);
- ETSI TS 102 176-1 replaced by ETSI TS 119 312 (effective date no later than 4 weeks after publication of PoR 4.3);
- Removal of requirement pkio95 due to duplicate with ETSI EN 319 411-1 (effective date no later than 4 weeks after publication of PoR 4.3);
- Use of values in BasicConstraints field no longer permitted in end entity certificates (effective date 1-7-2016);
- ETSI TS 102 042 replaced by ETSI EN 319 411-1 (effective date 1-7-2016 or when the accreditation to the certifying body has been granted with a final date of 30 June 2017).

Editorial

None.

1.2.1.4 Version 4.3 to 4.4

New

None.

Modifications

- Removal of requirement 5.3.2-pkio79 (effective date 1-2-2017);
- Clarification of issuer.organizationIdentifier field (effective date 1-2-2017);
- Tightening of use optional EKUs that conflict with the parent TSP CA certificate (effective date 1-2-2017).

Editorial

- Replaced CSP (Certificate Service Provider) with TSP (Trust Service Provider) in accordance with eIDAS directive.

1.2.1.5 Version 4.4 to 4.5

New

- Possibility to offer CPS in English and/or Dutch (requirement 2.2-pkio157, effective date 1-10-2017);
- Mandatory yearly renewal CPS (requirement 2.2-pkio156, effective date 1-1-2017).

Modifications

- Requirement 4.9.9-pkio67 now references RFC6960 instead of RFC2560 (effective date 31-12-2016);
- Change in OID 2.16.528.1.1003.1.2.8.4 to also cover OCSP responder certificates (effective date 1-7-2017);
- Mandatory use of field "NextUpdate" in OCSP responses (requirement 4.9.9-pkio71, effective date 1-7-2017).

Editorial

None.

1.2.1.6 Version 4.5 to 4.6

New

None.

Modifications

- Corrected subjectAltName.othername field (effective date directly after publication of PoR 4.6).

Editorial

None.

1.2.1.7 Version 4.6 to 4.7

New

- Requirement 7.1-pkio177 (effective date immediately after publication of PoR 4.7).

Modifications

- Description of a number of certificate attributes replaced by reference to requirement 7.1-pkio174 (effective date 8 weeks after publication of PoR 4.7);
- Reference to CWA 14 169 amended to EN 419 211 for QSCDs. This also sets requirements for the issuance of QSCDs for requirements 6.1.1-pkio88, 6.1.1-pkio93, 6.2.11-pkio105, 6.4.1-pkio112 and 4.9.1-pkio52 (effective date immediately after publication of PoR 4.7).

Editorial

None.

1.2.1.8 Version 4.7 to 4.8

New

- Requirement 3.2.2-pkio186 on (re)validation of organizational data (effective date directly after publication of PoR 4.8).

Modifications

- Change in requirement 7.1-pkio177 on serial number requirements (effective date August 29, 2019);
- Change in requirement 7.1-pkio150 to allow constraint (EKU emailProtection) in PoR (effective date directly after publication of PoR 4.8);
- Requirement 9.17-pkio140 removed (effective date directly after publication of PoR 4.8).

Editorial

- Change in definition of private key in requirement 4.9.1-pkio52 (effective date directly after publication of PoR 4.8).

1.2.1.9 Version 4.8 to 4.9

New

None.

Modifications

- Change requirement 6.1.1-pkio89 to comply with Mozilla policy on signature encoding (effective date 01-03-2020).

Removals

- Requirement 2.2-pkio8 has been removed (effective date immediately after publication PoR 4.9);
- Requirement 2.2-pkio157 has been removed (effective date immediately after publication PoR 4.9);
- Requirement 6.1.1-pkio87 has been removed (effective date immediately after publication PoR 4.9).

Editorial

None.

1.2.1.10 Version 4.9 to 4.10

New

- Added basic requirement 8.2-pkio199.
- Added new additional requirement 8.4-pkio196.

Modifications

- Change the description, explanation, and criterium of the `extensions:subjectAltName:otherName` attribute in the certificate profile.
- Changes to the `subject:organizationIdentifier` attribute in the certificate profile.
- Expand the description of the `extensions:certificatePolicies` field in the certificate profile with additional ETSI 319 411 certificate policies.
- Change the `extensions:certificatePolicies:policyQualifiers:qualifier:userNotice` field criteria to "MAY" in the certificate profile.
- Replace Telecommunications Act with eDIAS in requirement 9.6.1-pkio127.

Removals

- Remove the `subject:postalAddress` attribute from the certificate profile.

- Remove the `subject:organizationalUnitName` attribute from the certificate profile.
- Remove the `extensions:freshestCRL` field from the certificate profile.
- Remove the `extensions:subjectInfoAccess` field from the certificate profile.
- Remove requirement 9.6.1-pkio129.

Editorial

- Editorial changes in the description and explanation of the `extensions:certificatePolicies:policyQualifiers:qualifier:userNotice` field in the certificate profile resulting from combining change 450 with change 445.13.
- Expanded the description of the `extensions:basicConstraints` field in the certificate profile.
- Editorial changes to requirement 9.6.1-pkio127.

1.2.1.11 Version 4.10 to 4.11

New

None.

Modifications

None.

Removals

None.

Editorial

None.

1.2.2 Relevant dates

Version	Date	Description
4.0	12-2014	Ratified by the Ministry of the Interior and Kingdom Relations December 2014
4.1	07-2015	Ratified by the Ministry of the Interior and Kingdom Relations July 2015
4.2	01-2016	Ratified by the Ministry of the Interior and Kingdom Relations January 2016
4.3	07-2016	Ratified by the Ministry of the Interior and Kingdom Relations July 2016
4.4	02-2017	Ratified by the Ministry of the Interior and Kingdom Relations February 2017
4.5	07-2017	Ratified by the Ministry of the Interior and Kingdom Relations July 2017
4.6	01-2018	Ratified by the Ministry of the Interior and Kingdom Relations January 2018

4.7	01-2019	Ratified by the Ministry of the Interior and Kingdom Relations January 2019
4.8	02-2020	Ratified by the Ministry of the Interior and Kingdom Relations February 2020
4.9	02-2021	Ratified by the Ministry of the Interior and Kingdom Relations February 2021
4.10	02-2022	Ratified by the Ministry of the Interior and Kingdom Relations February 2022
4.11	02-2023	Ratified by the Ministry of the Interior and Kingdom Relations February 2023

1.3 PKI participants

1.3.1 Certification authorities

In this document the distinction is made between the term Certification Authority (CA) and Trust Service Provider. In international usage, "CA" is an umbrella term that refers to all entities authorized to issue, manage, revoke, and renew certificates. This can apply to the actual CA certificate as well as the organization. In this CP, the organization which holds a CA is referred to as a TSP. The term CA is used to refer to the infrastructure and keymaterial from which a TSP issues and signs certificates. This CP covers all certificates issued and signed by the following CAs hereinafter referred to as TSPs.

Common Name	Not Before	Not After	Serial Number	SHA256 Fingerprint
Digidentity BV PKIoverheid Private Services CA - G1 (3g+3h)	29 Nov 2018	12 Nov 2028	2784474161498963929	BFE8F634772B0EC2CD2A41A17 F7C612577D7E24F934073DEC8 9A991B6169687E
KPN PKIoverheid Private Services CA - G1 (3g+h)	25 Nov 2015	12 Nov 2028	1387491402357593400	BDB68500AAAE2563C57B45257 84360436D3E3FD8DF974B25A7 7F132CECC2A49D
QuoVadis PKIoverheid Private Services CA - G1 (3g+3h)	14 Nov 2016	12 Nov 2028	6011242634312924764	69DF8D18C54503F83DC239C3D CF8115B2A447EFC5DEFCA6119 D18E988C12276D
UZI-register Private Server CA G1 (3h)	09 Mar 2017	12 Nov 2028	5613314895991348523	BDD860EF8E87E2B2C7EBB34DD 6E9E1771A3A3C5DEC850BA708 0E3E2904DBD897
ZOVAR Private Server CA G1 (3h)	09 Mar 2017	12 Nov 2028	3936653012735493143	FE54263BC96C2DFBAC5BE5F44 9CFF7F5B12B6255A7BBCF761B A979E5986E1598

1.3.2 Registration authorities

Refer to Programme of Requirements part 3 Basic Requirements.

1.3.3 Subscribers

Refer to Programme of Requirements part 3 Basic Requirements.

1.3.4 Relying parties

Refer to Programme of Requirements part 3 Basic Requirements.

1.3.5 Other participants

Refer to Programme of Requirements part 3 Basic Requirements.

1.4 Certificate usage

1.4.1 Appropriate certificate uses

The use of certificates issued under this CP relates to communication from certificate holders who act on behalf of the subscriber.

[OID 2.16.528.1.1003.1.2.8.4]

Authenticity certificates, issued under this CP, can be used to identify and authenticate, by electronic means, the service that is part of the organizational entity, which is responsible for the relevant service. Issuance of code signing certificates by means of which the integrity and authenticity of software can be safeguarded by a digital signature being placed are NOT allowed under this CP.

Under this OID OCSF responder certificates may be issued for use within the domain Private Services. Said certificates can be used to sign OCSF responses for use in the verification of the validity of the end user certificate. More information can be obtained in appendix A of the base requirements.

[OID 2.16.528.1.1003.1.2.8.5]

Confidentiality certificates, issued under this CP, can be used to protect the confidentiality of data that is exchanged and/or stored in an electronic format.

1.4.2 Prohibited certificate uses

Refer to Programme of Requirements part 3 Basic Requirements.

1.5 Policy administration

1.5.1 Organization administering the document

The Ministry of Interior and Kingdom Relations (BZK) is responsible for this CPS. BZK has delegated this responsibility to Logius, including approval of changes of this document.

1.5.2 Contact person

Policy Authority PKIoverheid
Wilhelmina van Pruisenweg 52
Postbus 96810
2509 JE DEN HAAG
<http://www.logius.nl/pkioverheid>
servicecentrum@logius.nl¹

1.5.3 Person determining CPS suitability for the policy

The Policy Authority PKIoverheid (PA) determines the suitability of CPSs published as a result of this CP.

¹ <mailto:servicecentrum@logius.nl>

1.5.4 CP approval procedures

The PA PKIoverheid reserves the right to amend this CP. Changes are applicable from the date that is listed in section *1.2.2. Relevant dates*. The management of Logius is responsible for following the procedures as listed in section *9.12 Amendments* and final approval of this CP.

1.6 Definitions and acronyms

1.6.1 Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in these Requirements MUST be interpreted in accordance with RFC 2119.

2. PUBLICATION AND REPOSITORY RESPONSIBILITIES

2.1 Repositories

Refer to Programme of Requirements part 3 Basic Requirements.

2.2 Publication of certification information

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
2.2-pkio3 —

Description	The CPS MUST be available in English. If a CPS is published in multiple languages there MUST be no substantial substantive difference between the different versions. In case of interpretation disputes related to CPS texts the English language version SHALL always be leading.
Comment	-

2.3 Time or frequency of publication

Refer to Programme of Requirements part 3 Basic Requirements.

2.4 Access controls on repositories

Refer to Programme of Requirements part 3 Basic Requirements.

3. IDENTIFICATION AND AUTHENTICATION

3.1 Naming

3.1.1 Types of names

Refer to Programme of Requirements part 3 Basic Requirements.

3.1.2 Need for names to be meaningful

Refer to Programme of Requirements part 3 Basic Requirements.

3.1.3 Anonymity or pseudonymity of subscribers

Refer to Programme of Requirements part 3 Basic Requirements.

3.1.4 Rules for interpreting various name forms

Refer to Programme of Requirements part 3 Basic Requirements.

3.1.5 Uniqueness of names

Refer to Programme of Requirements part 3 Basic Requirements.

3.1.6 Recognition, authentication, and role of trademarks

Refer to Programme of Requirements part 3 Basic Requirements.

3.2 Initial identity validation

3.2.1 Method to prove possession of private key

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
3.2.1-pkio13 —

Description	<p>The TSP is responsible for ensuring that the subscriber supplies the certificate signing request (CSR) securely. The secure delivery must take place in the following manner:</p> <ul style="list-style-type: none">• the entry of the CSR on the TSP's application developed especially for that purpose, using an SSL connection with a PKIoverheid SSL certificate or similar or;• the entry of the CSR on the HTTPS website of the TSP that uses a PKIoverheid SSL certificate or similar or;• sending the CSR by e-mail, along with a qualified electronic signature of the certificate manager that uses a PKIoverheid qualified certificate or similar or;• entering or sending a CSR in a way that is at least equivalent to the aforementioned ways.
Comment	-

3.2.2 Authentication of organization identity

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
3.2.2-pkio144 —

Description	The TSP has to verify that the name of the organization registered by the subscriber that is incorporated in the certificate is correct and complete
Comment	-

- Page:
3.2.2-pkio186 —

Description	If an organization changes its name but the underlying registration number (e.g. HRN) remains the same, then the subscriber DOES NOT have to go through the subscription registration again. If the organization name remains the same but the underlying registration number changes, then the TSP MUST perform the subscription registration again. In both cases, the existing certificate must be withdrawn because the data in the certificate no longer conforms to the originally validated data.
Comment	-

- Page:
3.2.2-pkio4 —

Description	The TSP has to verify that the subscriber is an existing organization.
Comment	-

3.2.3 Authentication of individual identity

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
3.2.3-pkio22 —

Description	In accordance with Dutch legislation and regulations, the TSP has to check the identity and, if applicable, specific properties of the certificate manager. Proof of identity has to be verified based on the physical appearance of the person himself, either directly or indirectly, using means by which the same certainty can be obtained as with personal presence. The proof of identity can be supplied on paper or electronically.
Comment	-

- Page:
3.2.3-pkio24 —

Description	The identity of the certificate manager can only be established using the valid documents referred to in article 1 of the Compulsory Identification Act (Wet op de identificatieplicht). The TSP has to check the validity and authenticity of these documents.
Comment	If the personal identity of the certificate manager is verified when a certificate is requested in the Government, Companies and Organization Domains, then the identity verification of the certificate manager will be considered to have taken place under this CP.

- Page:
3.2.3-pkio26 —

Description	<p>The certificate manager is a person whose identity has to be established in conjunction with an organizational entity. Proof has to be submitted of:</p> <ul style="list-style-type: none"> • full name, including surname, first name, initials or other first (names) (if applicable) and surname prefixes (if applicable); • date of birth and place of birth, a nationally applicable registration number, or other characteristics of the certificate manager that can be used in order to, as far as possible, distinguish this person from other persons with the same name; • proof that the certificate manager is entitled to receive a certificate for a certificate holder on behalf of the legal personality or other organizational entity.
Comment	-

3.2.4 Non-verified subscriber information

Refer to Programme of Requirements part 3 Basic Requirements.

3.2.5 Validation of authority

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
3.2.5-pkio30 —

Description	<p>The TSP has to verify that:</p> <ul style="list-style-type: none"> • the proof that the certificate holder is authorized to receive a certificate on behalf of the subscriber, is authentic; • the certificate manager has received permission from the subscriber to perform the actions that he has been asked to perform (if the certificate manager performs the registration process).
Comment	The "certificate manager" who takes over those actions from the certificate holder does not necessarily have to be the same person as the system administrator or personnel officer. Also the knowledge of the activation data of the key material (for example PIN) can be shared by various people if the organization of the certificate management requires that. However, it is recommended that as few people as possible have knowledge of the PIN. It also would be wise to take measures that limit access to the PIN. An example of this is placing the PIN in a safe to which only authorized persons can gain access in certain situations.

- Page:
3.2.5-pkio33 —

Description	The agreement that the TSP enters into with the subscriber has to state that the subscriber is responsible for immediately informing the TSP of any relevant changes to the relationship between the subscriber and certificate manager and/or service. When the service no longer exists, this has to take place by means of a revocation request.
Comment	-

3.2.6 Criteria for interoperation

Refer to Programme of Requirements part 3 Basic Requirements.

3.3 Identification and authentication for re-key requests

3.3.1 Identification and authentication for routine re-key

Refer to Programme of Requirements part 3 Basic Requirements.

3.3.2 Identification and authentication for re-key after revocation

Refer to Programme of Requirements part 3 Basic Requirements.

3.4 Identification and authentication for revocation request

Refer to Programme of Requirements part 3 Basic Requirements.

4. CERTIFICATE LIFE-CYCLE OPERATIONAL REQUIREMENTS

4.1 Certificate Application

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
4.1-pkio47 –

Description	Before a services server certificate is issued, the TSP must enter into an agreement with the subscriber and receive a certificate request signed by the certificate manager. The agreement must be signed by the Authorized Representative or Representation of the subscriber.
Comment	-

4.1.1 Who can submit a certificate application

Refer to Programme of Requirements part 3 Basic Requirements.

4.1.2 Enrollment process and responsibilities

Refer to Programme of Requirements part 3 Basic Requirements.

4.2 Certificate application processing

4.2.1 Performing identification and authentication functions

Refer to Programme of Requirements part 3 Basic Requirements.

4.2.2 Approval or rejection of certificate applications

Refer to Programme of Requirements part 3 Basic Requirements.

4.2.3 Time to process certificate applications

Refer to Programme of Requirements part 3 Basic Requirements.

4.3 Certificate issuance

4.3.1 CA actions during certificate issuance

Refer to Programme of Requirements part 3 Basic Requirements.

4.3.2 Notification to subscriber by the CA of issuance of Certificate

Refer to Programme of Requirements part 3 Basic Requirements.

4.4 Certificate acceptance

4.4.1 Conduct constituting certificate acceptance

Refer to Programme of Requirements part 3 Basic Requirements.

4.4.2 Publication of the certificate by the CA

Refer to Programme of Requirements part 3 Basic Requirements.

4.4.3 Notification of certificate issuance by the CA to other Entities

Refer to Programme of Requirements part 3 Basic Requirements.

4.5 Key pair and certificate usage

4.5.1 Subscriber private key and certificate usage

Refer to Programme of Requirements part 3 Basic Requirements.

4.5.2 Relying party public key and certificate usage

Refer to Programme of Requirements part 3 Basic Requirements.

4.6 Certificate renewal

4.6.1 Circumstance for certificate renewal

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.2 Who may request renewal

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.3 Processing certificate renewal requests

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.4 Notification of new certificate issuance to subscriber

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.5 Conduct constituting acceptance of a renewal certificate

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.6 Publication of the renewal certificate by the CA

Refer to Programme of Requirements part 3 Basic Requirements.

4.6.7 Notification of certificate issuance by the CA to other entities

Refer to Programme of Requirements part 3 Basic Requirements.

4.7 Certificate re-key

4.7.1 Circumstance for certificate re-key

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.2 Who may request certification of a new public key

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.3 Processing certificate re-keying requests

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.4 Notification of new certificate issuance to subscriber

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.5 Conduct constituting acceptance of a re-keyed certificate

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.6 Publication of the re-keyed certificate by the CA

Refer to Programme of Requirements part 3 Basic Requirements.

4.7.7 Notification of certificate issuance by the CA to other entities

Refer to Programme of Requirements part 3 Basic Requirements.

4.8 Certificate modification

4.8.1 Circumstance for certificate modification

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.2 Who may request certificate modification

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.3 Processing certificate modification requests

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.4 Notification of new certificate issuance to subscriber

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.5 Conduct constituting acceptance of modified certificate

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.6 Publication of the modified certificate by the CA

Refer to Programme of Requirements part 3 Basic Requirements.

4.8.7 Notification of certificate issuance by the CA to other entities

Refer to Programme of Requirements part 3 Basic Requirements.

4.9 Certificate revocation and suspension

4.9.1 Circumstances for revocation

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:

4.9.1-pkio52 —

Description	<p>Certificates must be revoked when:</p> <ul style="list-style-type: none"> • the subscriber states that the original request for a certificate was not allowed and the subscriber does not provide consent with retrospective force; • the TSP has sufficient proof that the subscriber's private key (that corresponds with the public key in the certificate) is compromised or if compromise is suspected, or if there is inherent security vulnerability, or if the certificate has been misused in any other way. A key is considered to be compromised in the event of unauthorized access or suspected unauthorized access to the private key, if the private key, SSCD, SUD or QSCD, is lost or suspected to be lost, if the key, SSCD, SUD or QSCD, is stolen or suspected to be stolen, or if the key or SSCD, SUD or QSCD is destroyed; • a subscriber does not fulfil its obligations outlined in this CP or the corresponding CPS of the TSP or the agreement that the TSP has entered into with the subscriber; • the TSP is informed or otherwise becomes aware of a substantial change in the information that is provided in the certificate. An example of that is: a change in the name of the certificate holder; • the TSP determines that the certificate has not been issued in line with this CP or the corresponding CPS of the TSP or the agreement that the TSP has entered into with the subscriber; • the TSP determines that information in the certificate is incorrect or misleading; • the TSP ceases its work and the CRL and OCSP services are not taken over by a different TSP. • the PA of PKIoverheid determines that the technical content of the certificate entails an irresponsible risk to subscribers, relying parties and third parties (e.g. browser parties).
Comment	<p>In addition, certificates can be revoked as a measure to prevent or to combat an emergency. Considered to be an emergency is definitely the compromise or suspected compromise of the private key of the TSP used to sign certificates.</p>

4.9.2 Who can request revocation

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.3 Procedure for revocation request

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
4.9.3-pkio57 —

Description	<p>In any case, the TSP has to use a CRL to make the certificate status information available.</p>
Comment	<p>-</p>

4.9.4 Revocation request grace period

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.5 Time within which CA must process the revocation request

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.6 Revocation checking requirement for relying parties

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.7 CRL issuance frequency (if applicable)

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
4.9.7-pkio65 —

Description	The TSP has to update and reissue the CRL for end user certificates at least once every 7 calendar days and the date of the "Next update" field may not exceed the date of the "Effective date" field by 10 calendar days.
Comment	-

4.9.8 Maximum latency for CRLs (if applicable)

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.9 On-line revocation/status checking availability

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
4.9.9-pkio66 —

Description	The revocation management services of the TSP can support the Online Certificate Status Protocol (OCSP) as an addition to the publication of CRL information. If this support is available, this has to be stated in the CPS.
Comment	<p>If OCSP is offered the following requirements are applicable:</p> <ul style="list-style-type: none"> • 1.1-pkio10 (basic requirement) • 9.5-pkio61 (basic requirement) • 9.9-pkio67 • 9.9-pkio68 • 9.5-pkio69 (basic requirement) • 9.9-pkio70 • 9.9-pkio71 • 10.2-pkio73 (basic requirement) <p>NB: (EV) server certificates MUST use OCSP services as stipulated in ETSI EN 319 411-1 and the Baseline Requirements.</p>

- Page:

4.9.9-pkio67 —

Description	If the TSP supports the Online Certificate Status Protocol (OCSP), this must conform to IETF RFC 6960.
Comment	-

- Page:

4.9.9-pkio70 —

Description	If the TSP supports OCSP, the information that is provided through OCSP has to be at least as equally up-to-date and reliable as the information that is published by means of a CRL, during the validity of the certificate that is issued and furthermore up to at least six months after the time at which the validity of the certificate has expired or, if that time is earlier, after the time at which the validity is ended by revocation.
Comment	-

- Page:

4.9.9-pkio71 —

Description	If the TSP supports OCSP, the TSP has to update the OCSP service at least once every 4 calendar days. The maximum expiry term of the OCSP responses is 10 calendar days. In addition OCSP responses must contain the "nextUpdate" field in conformance to RFC6960.
Comment	-

4.9.10 On-line revocation checking requirements

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.11 Other forms of revocation advertisements available

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.12 Special requirements related to key compromise

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.13 Circumstances for suspension

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.14 Who can request suspension

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.15 Procedure for suspension request

Refer to Programme of Requirements part 3 Basic Requirements.

4.9.16 Limits on suspension period

Refer to Programme of Requirements part 3 Basic Requirements.

4.10 Certificate status services

4.10.1 Operational characteristics

Refer to Programme of Requirements part 3 Basic Requirements.

4.10.2 Service availability

Refer to Programme of Requirements part 3 Basic Requirements.

4.10.3 Optional features

Refer to Programme of Requirements part 3 Basic Requirements.

4.11 End of subscription

Refer to Programme of Requirements part 3 Basic Requirements.

4.12 Key escrow and recovery

4.12.1 Key escrow and recovery policy and practices

Refer to Programme of Requirements part 3 Basic Requirements.

4.12.2 Session key encapsulation and recovery policy and practices

Refer to Programme of Requirements part 3 Basic Requirements.

5. FACILITY, MANAGEMENT, AND OPERATIONAL CONTROLS

5.1 Physical controls

5.1.1 *Site location and construction*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.2 *Physical access*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.3 *Power and air conditioning*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.4 *Water exposures*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.5 *Fire prevention and protection*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.6 *Media storage*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.7 *Waste disposal*

Refer to Programme of Requirements part 3 Basic Requirements.

5.1.8 *Off-site backup*

Refer to Programme of Requirements part 3 Basic Requirements.

5.2 Procedural controls

5.2.1 *Trusted roles*

Refer to Programme of Requirements part 3 Basic Requirements.

5.2.2 *Number of persons required per task*

Refer to Programme of Requirements part 3 Basic Requirements.

5.2.3 *Identification and authentication for each role*

Refer to Programme of Requirements part 3 Basic Requirements.

5.2.4 *Roles requiring separation of duties*

Refer to Programme of Requirements part 3 Basic Requirements.

5.3 Personnel controls

5.3.1 Qualifications, experience, and clearance requirements

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.2 Background check procedures

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.3 Training requirements

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.4 Retraining frequency and requirements

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.5 Job rotation frequency and sequence

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.6 Sanctions for unauthorized actions

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.7 Independent contractor requirements

Refer to Programme of Requirements part 3 Basic Requirements.

5.3.8 Documentation supplied to personnel

Refer to Programme of Requirements part 3 Basic Requirements.

5.4 Audit logging procedures

5.4.1 Types of events recorded

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
5.4.1-pkio80 —

Description	<p>Logging has to take place on at least:</p> <ul style="list-style-type: none"> • Routers, firewalls and network system components; • Database activities and events; • Transactions; • Operating systems; • Access control systems; • Mail servers. <p>At the very least, the TSP has to log the following events:</p> <ul style="list-style-type: none"> • CA key life cycle management; • Certificate life cycle management; • Threats and risks such as: <ul style="list-style-type: none"> • Successful and unsuccessful attacks on the PKI system; • Activities of staff on the PKI system; • Reading, writing and deleting data; • Profile changes (Access Management); • System failure, hardware failure and other abnormalities; • Firewall and router activities; • Entering and leaving the CA space. <p>At the very least, the log files have to register the following:</p> <ul style="list-style-type: none"> • Source addresses (IP addresses if available); • Destination addresses (IP addresses if available); • Time and date; • User IDs (if available); • Name of the incident; • Description of the incident.
Comment	Based on a risk analysis the TSP determines which data it should save.

5.4.2 Frequency of processing log

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.3 Retention period for audit log

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.4 Protection of audit log

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.5 Audit log backup procedures

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.6 Audit collection system (internal vs. external)

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.7 Notification to event-causing subject

Refer to Programme of Requirements part 3 Basic Requirements.

5.4.8 Vulnerability assessments

Refer to Programme of Requirements part 3 Basic Requirements.

5.5 Records archival

5.5.1 Types of records archived

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
5.5.1-pkio82 —

Description	The TSP MUST archive all information used to verify the identity of the subscriber, certificate manager and applicants of revocation requests. This information includes reference numbers of the documentation used for verification, including limitations concerning the validity.
Comment	-

5.5.2 Retention period for archive

Refer to Programme of Requirements part 3 Basic Requirements.

5.5.3 Protection of archive

Refer to Programme of Requirements part 3 Basic Requirements.

5.5.4 Archive backup procedures

Refer to Programme of Requirements part 3 Basic Requirements.

5.5.5 Requirements for time-stamping of records

Refer to Programme of Requirements part 3 Basic Requirements.

5.5.6 Archive collection system (internal or external)

Refer to Programme of Requirements part 3 Basic Requirements.

5.5.7 Procedures to obtain and verify archive information

Refer to Programme of Requirements part 3 Basic Requirements.

5.6 Key changeover

Refer to Programme of Requirements part 3 Basic Requirements.

5.7 Compromise and disaster recovery

5.7.1 Incident and compromise handling procedures

Refer to Programme of Requirements part 3 Basic Requirements.

5.7.2 Computing resources, software, and_or data are corrupted

Refer to Programme of Requirements part 3 Basic Requirements.

5.7.3 Entity private key compromise procedures

Refer to Programme of Requirements part 3 Basic Requirements.

5.7.4 Business continuity capabilities after a disaster

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
5.7.4-pkio86 —

Description	<p>The TSP has to draw up a business continuity plan (BCP) for, at the very least, the core services dissemination service, revocation management service and revocation status service, the aim being, in the event of a security breach or emergency, to inform, reasonably protect and to continue the TSP services for subscribers, relying parties and third parties (including browser parties). The TSP has to test, assess and update the BCP annually. At the very least, the BCP has to describe the following processes:</p> <ul style="list-style-type: none"> • Requirements relating to entry into force; • Emergency procedure/fall-back procedure; • Requirements relating to restarting TSP services; • Maintenance schedule and test plan that cover the annual testing, assessment and update of the BCP; • Provisions in respect of highlighting the importance of business continuity; • Tasks, responsibilities and competences of the involved agents; • Intended Recovery Time or Recovery Time Objective (RTO); • Recording the frequency of back-ups of critical business information and software; • Recording the distance of the fall-back facility to the TSP's main site; and • Recording the procedures for securing the facility during the period following a security breach or emergency and for the organization of a secure environment at the main site or fall-back facility.
Comment	-

5.8 CA or RA termination

Refer to Programme of Requirements part 3 Basic Requirements.

6. TECHNICAL SECURITY CONTROLS

6.1 Key pair generation and installation

6.1.1 Key pair generation

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
6.1.1-pkio88 —

Description	The keys of certificate holders (or data for creating electronic signatures) have to be generated using a device that fulfils the requirements mentioned in EN 419 211 for QSCD's or CWA 14169 for SSCD's (transitional permission regime) "Secure signature-creation devices "EAL 4+" or comparable security criteria.
Comment	-

- Page:
6.1.1-pkio89 —

Description	The algorithm and length of the cryptographic keys that the TSP uses to generate the keys of certificate holders must meet the requirements set in the list of cryptographic algorithms and key lengths, as defined in ETSI TS 119 312. In addition, the TSP must also follow the requirements described in Chapters 5.1 and 5.1.1 of the most current Mozilla Root Store Policy. The use of RSA-PSS is permitted, but is not recommended.
Comment	Although ETSI TS 119 312 outlines the recommended algorithms and key lengths, these are compulsory within the PKI for the government. Requests relating to the use of other algorithms have to be submitted, along with the reasoning behind this, to the PA of the PKI for the government.

- Page:
6.1.1-pkio92 —

Description	A TSP within PKIoverheid is not allowed to issue code signing certificates.
Comment	-

- Page:
6.1.1-pkio93 —

Description	<p>Instead of the TSP generating the keys, the certificate manager MAY generate the keys of the services authenticity and encryption certificates in a SUD using PKCS#10 to deliver the CSR to the TSP for signing, under the following conditions:</p> <ul style="list-style-type: none"> • The agreement between the TSP and the subscriber stipulates that the certificate manager generates, saves and uses the private key on a secure device that conforms to the requirements of CWA 14169 for a Secure signature-creation devices or EN 419 211 for Qualified signature-creation devices "EAL 4+" or comparable security criteria. <p>With the request the subscriber must prove that the secure device used for key generation conforms to CWA 14169 for a Secure signature-creation devices or EN 419 211 for Qualified signature-creation devices EAL 4+" or comparable security criteria.</p> <p>The TSP must then verify that the SUD in question conforms (comparable to "The subscriber MUST prove that the organization may use this name.")</p> <ul style="list-style-type: none"> • On registration the certificate manager must at least produce a written statement that measures have been taken in the environment of the system that generates/contains the keys. The measures must be of such quality that is practically impossible to steal or copy the keys unnoticed. <p>The agreement between the subscriber and the TSP must stipulate that the TSP has the right to perform an audit on the measures taken (conform 6.2.11-pkio107)</p> <ul style="list-style-type: none"> • The agreement between the subscriber and the TSP must contain the following condition. The subscriber must declare that the private key (and the corresponding access information such as a PIN code), relating to the public key in het SUD in question has, in an appropriate manner, been generated under the control of the certificate manager and will be kept secret and protected in the future.
Comment	-

6.1.2 Private key delivery to subscriber

Refer to Programme of Requirements part 3 Basic Requirements.

6.1.3 Public key delivery to certificate issuer

Refer to Programme of Requirements part 3 Basic Requirements.

6.1.4 CA public key delivery to relying parties

Refer to Programme of Requirements part 3 Basic Requirements.

6.1.5 Key sizes

Refer to Programme of Requirements part 3 Basic Requirements.

6.1.6 Public key parameters generation and quality checking

Refer to Programme of Requirements part 3 Basic Requirements.

6.1.7 Key usage purposes (as per X.509 v3 key usage field)

Refer to Programme of Requirements part 3 Basic Requirements.

6.2 Private Key Protection and Cryptographic Module Engineering Controls

6.2.1 Cryptographic module standards and controls

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.2 Private key (n out of m) multi-person control

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.3 Private key escrow

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
6.2.3-pkio100 —

Description	The TSP has to describe in the CPS which parties can have access to the private key of the confidentiality certificate held in Escrow and under which conditions.
Comment	-

- Page:
6.2.3-pkio99 —

Description	The authorized persons who can gain access to the private key of the confidentiality certificate held in Escrow by the TSP (if applicable), have to identify themselves using the valid documents listed in article 1 of the Compulsory Identification Act (Wet op de identificatieplicht), or a valid qualified certificate (limited to a PKIoverheid signature certificate or equivalent).
Comment	-

6.2.4 Private key backup

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.5 Private key archival

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.6 Private key transfer into or from a cryptographic module

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.7 Private key storage on cryptographic module

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.8 Method of activating private key

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.9 Method of deactivating private key

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.10 Method of destroying private key

Refer to Programme of Requirements part 3 Basic Requirements.

6.2.11 Cryptographic Module Rating

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
6.2.11-pkio105 —

Description	Instead of demonstrating compliance with CWA 14169 (for SSCD's or SUD's) or EN 419 211 (for QSCD's), TSPs can issue or recommend SSCDs, SUDs or QSCDs that are certified in line with a different protection profile against the Common Criteria (ISO/IEC 15408) at level EAL4+ or that have a comparable security level. This has to be established by a test laboratory that is accredited for performing Common Criteria evaluations.
Comment	-

- Page:
6.2.11-pkio125 —

Description	Secure devices issued or recommended by the TSP for storage of keys (SUDs) have to fulfil the requirements laid down in document CWA 14169 "Secure signature-creation devices "EAL 4+""
Comment	-

6.3 Other aspects of key pair management

6.3.1 Public key archival

Refer to Programme of Requirements part 3 Basic Requirements.

6.3.2 Certificate operational periods and key pair usage periods

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
6.3.2-pkio109 —

Description	Private keys that are used by a certificate holder and issued under the responsibility of this CP must not be used for more than five years. The certificates, which are issued under the responsibility of this CP, must not be valid for more than five years.
Comment	-

6.4 Activation data

6.4.1 Activation data generation and installation

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
6.4.1-pkio112 —

Description	The TSP attaches activation data to the use of a SUD, SSCD or QSCD, to protect the private keys of the certificate holders.
Comment	The requirements that the activation data (for example the PIN code) have to fulfil can be determined by the TSPs themselves based on, for example, a risk analysis. Requirements that could be considered are the length of the PIN code and use of special characters.

- Page:
6.4.1-pkio113 —

Description	An unlocking code can only be used if the TSP can guarantee that, at the very least, the security requirements are fulfilled that are laid down in respect of the use of the activation data.
Comment	-

6.4.2 Activation data protection

Refer to Programme of Requirements part 3 Basic Requirements.

6.4.3 Other aspects of activation data

Refer to Programme of Requirements part 3 Basic Requirements.

6.5 Computer security controls

6.5.1 Specific computer security technical requirements

Refer to Programme of Requirements part 3 Basic Requirements.

6.5.2 Computer security rating

Refer to Programme of Requirements part 3 Basic Requirements.

6.6 Life cycle technical controls

6.6.1 System development controls

Refer to Programme of Requirements part 3 Basic Requirements.

6.6.2 Security management controls

Refer to Programme of Requirements part 3 Basic Requirements.

6.6.3 Life cycle security controls

Refer to Programme of Requirements part 3 Basic Requirements.

6.7 Network security controls

6.7.1 Network security controls (duplicate)

Refer to Programme of Requirements part 3 Basic Requirements.

6.8 Time-stamping

Refer to Programme of Requirements part 3 Basic Requirements.

7. CERTIFICATE, CRL, AND OCSP PROFILES

7.1 Certificate profile

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
7.1-pkio150 —

Description	<p>The certificate extension Extended Key Usage MUST be present, MUST NOT be marked "critical", and MUST contain at least the following KeyPurposeIds:</p> <p>For a services authentication certificate:</p> <ul style="list-style-type: none"> • client Authentication =1.3.6.1.5.5.7.3.2 • document Signing =1.3.6.1.4.1.311.10.3.12 • emailProtection =1.3.6.1.5.5.7.3.4 <p>For a services confidentiality certificate:</p> <ul style="list-style-type: none"> • Encrypting File System =1.3.6.1.4.1.311.10.3.4 • emailProtection = 1.3.6.1.5.5.7.3.4 <p>For a seal certificate</p> <ul style="list-style-type: none"> • document Signing =1.3.6.1.4.1.311.10.3.12 • emailProtection = 1.3.6.1.5.5.7.3.4 <p>The KeyPurposeId id-kp-serverAuth MUST NOT be present, the KeyPurposeId id-kp-codeSigning MUST NOT be present, the KeyPurposeId AnyextendedKeyusage MUST NOT be present and any KeyPurposeId solely intended to identify a service based on its FQDN MUST NOT be present.</p> <p>Specifically for G2 certificates any other KeyPurposeId defined in an open or accepted standard corresponding to the key usage as indicated by the KeyUsage extension MAY be present. In the G3 and following generations this extension MAY NOT be present.</p> <p>The above should take into account the EKUs included in the issuing TSP CA. If the issuing TSP CA is not provided with the mandatory EKUs stated above, these MAY NOT be included in the end-user certificate.</p>
Comment	-

- Page:
7.1-pkio177 —

Description	<p>The serial number of all end-user certificates must meet the following requirements:</p> <ol style="list-style-type: none"> The value of the serial number MUST NOT be 0 (zero) The value of the serial number MUST NOT be negative The value of the serial number MUST be unique within the population of end-user certificates issued under an issuing TSP CA. The serial number MUST have a minimum length of 96 bits (12 octets) The value of the serial number MUST contain at least 64 bits of unpredictable random data Said random data SHOULD be generated by a Cryptographically Secure Pseudorandom Number Generator (CSPRNG). The serial number MUST NOT be longer than 160 bits (20 octets).
Comment	-

7.1.1 Version number(s)

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.2 Certificate extensions

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.3 Algorithm object identifiers

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.4 Name forms

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.5 Name constraints

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.6 Certificate policy object identifier

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.7 Usage of Policy Constraints extension

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.8 Policy qualifiers syntax and semantics

Refer to Programme of Requirements part 3 Basic Requirements.

7.1.9 Processing semantics for the critical Certificate Policies extension

Refer to Programme of Requirements part 3 Basic Requirements.

7.2 CRL profile

7.2.1 Version number(s)

Refer to Programme of Requirements part 3 Basic Requirements.

7.2.2 CRL and CRL entry extensions

Refer to Programme of Requirements part 3 Basic Requirements.

7.3 OCSP profile

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
7.3-pkio123 —

Description	If the TSP supports the Online Certificate Status Protocol (OCSP), the TSP has to use OCSP certificates and responses in accordance with the requirements laid down in this respect in appendix A of the Basic Requirements, "CRL and OCSP certificate Profiles for certificate status information".
Comment	-

7.3.1 Version number(s)

Refer to Programme of Requirements part 3 Basic Requirements.

7.3.2 OCSP extensions

Refer to Programme of Requirements part 3 Basic Requirements.

8. COMPLIANCE AUDIT AND OTHER ASSESSMENTS

8.1 Frequency or circumstances of assessment

Refer to Programme of Requirements part 3 Basic Requirements.

8.2 Identity/qualifications of assessor

Refer to Programme of Requirements part 3 Basic Requirements.

8.3 Assessors relationship to assessed entity

Refer to Programme of Requirements part 3 Basic Requirements.

8.4 Topics covered by assessment

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
8.4-pkio196 —

Description	In addition to this PoR, issuing certificates SHALL undergo an audit in accordance with the following schemes: <ul style="list-style-type: none">a. ETSI EN 319 411-1 with policy NCP+ (ETSI CP OID 0.4.0.2042.1.2, mandating usage of SSCDs) for authenticity and confidentiality certificates, andb. CA/Browser Forum Network and Certificate System Security Requirements.
Comment	-

8.5 Actions taken as a result of deficiency

Refer to Programme of Requirements part 3 Basic Requirements.

8.6 Communication of results

Refer to Programme of Requirements part 3 Basic Requirements.

9. OTHER BUSINESS AND LEGAL MATTERS

9.1 Fees

9.1.1 Certificate issuance or renewal fees

Refer to Programme of Requirements part 3 Basic Requirements.

9.1.2 Certificate access fees

Refer to Programme of Requirements part 3 Basic Requirements.

9.1.3 Revocation or status information access fees

Refer to Programme of Requirements part 3 Basic Requirements.

9.1.4 Fees for other services

Refer to Programme of Requirements part 3 Basic Requirements.

9.1.5 Refund policy

Refer to Programme of Requirements part 3 Basic Requirements.

9.2 Financial responsibility

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
9.2-pkio124 —

Description	By means, for example, of insurance or its financial position, the TSP has to be able to cover third party recovery based on the types of liability mentioned in article 6:196b of the Civil Code (that relate to both direct and indirect damage) up to at least EUR 1,000,000 per annum.
Comment	The third party recovery described above is based on a maximum number of certificates to be issued of 100,000 for each TSP, which is in line with the current situation. When TSPs are going to issue more certificates, it will be determined whether a suitable, higher, recoverableness will be required.

9.2.1 Insurance coverage

Refer to Programme of Requirements part 3 Basic Requirements.

9.2.2 Other assets

Refer to Programme of Requirements part 3 Basic Requirements.

9.2.3 Insurance or warranty coverage for end-entities

Refer to Programme of Requirements part 3 Basic Requirements.

9.3 Confidentiality of business information

9.3.1 Scope of confidential information

Refer to Programme of Requirements part 3 Basic Requirements.

9.3.2 Information not within the scope of confidential information

Refer to Programme of Requirements part 3 Basic Requirements.

9.3.3 Responsibility to protect confidential information

Refer to Programme of Requirements part 3 Basic Requirements.

9.4 Privacy of personal information

9.4.1 Privacy plan

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.2 Information treated as private

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.3 Information not deemed private

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.4 Responsibility to protect private information

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.5 Notice and consent to use private information

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.6 Disclosure pursuant to judicial or administrative process

Refer to Programme of Requirements part 3 Basic Requirements.

9.4.7 Other information disclosure circumstances

Refer to Programme of Requirements part 3 Basic Requirements.

9.5 Intellectual property rights

Refer to Programme of Requirements part 3 Basic Requirements.

9.6 Representations and warranties

9.6.1 CA representations and warranties

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
9.6.1-pkio132 —

Description	The TSP excludes all liability for damages if the certificate is not used in accordance with the certificate use described in paragraph 1.4.
Comment	-

9.6.2 RA representations and warranties

Refer to Programme of Requirements part 3 Basic Requirements.

9.6.3 Subscriber representations and warranties

Refer to Programme of Requirements part 3 Basic Requirements.

9.6.4 Relying party representations and warranties

Refer to Programme of Requirements part 3 Basic Requirements.

9.6.5 Representations and warranties of other participants

Refer to Programme of Requirements part 3 Basic Requirements.

9.7 Disclaimers of warranties

Refer to Programme of Requirements part 3 Basic Requirements.

9.8 Limitations of liability

Refer to Programme of Requirements part 3 Basic Requirements.

Additional requirements:

- Page:
9.8-pkio133 —

Description	Within the scope of certificates as mentioned in paragraph 1.4 in this CP the TSP is not allowed to place restrictions on the use of certificates.
Comment	-

9.9 Indemnities

Refer to Programme of Requirements part 3 Basic Requirements.

9.10 Term and termination

9.10.1 Term

Refer to Programme of Requirements part 3 Basic Requirements.

9.10.2 Termination

Refer to Programme of Requirements part 3 Basic Requirements.

9.10.3 Effect of termination and survival

Refer to Programme of Requirements part 3 Basic Requirements.

9.11 Individual notices and communications with participants

Refer to Programme of Requirements part 3 Basic Requirements.

9.12 Amendments

9.12.1 Procedure for amendment

Refer to Programme of Requirements part 3 Basic Requirements.

9.12.2 Notification mechanism and period

Refer to Programme of Requirements part 3 Basic Requirements.

9.12.3 Circumstances under which OID must be changed

Refer to Programme of Requirements part 3 Basic Requirements.

9.13 Dispute resolution provisions

Refer to Programme of Requirements part 3 Basic Requirements.

9.14 Governing law

Refer to Programme of Requirements part 3 Basic Requirements.

9.15 Compliance with applicable law

Refer to Programme of Requirements part 3 Basic Requirements.

9.16 Miscellaneous provisions

9.16.1 Entire agreement

Refer to Programme of Requirements part 3 Basic Requirements.

9.16.2 Assignment

Refer to Programme of Requirements part 3 Basic Requirements.

9.16.3 Severability

Refer to Programme of Requirements part 3 Basic Requirements.

9.16.4 Enforcement (attorneys' fees and waiver of rights)

Refer to Programme of Requirements part 3 Basic Requirements.

9.16.5 Force Majeure

Refer to Programme of Requirements part 3 Basic Requirements.

9.17 Other provisions

Refer to Programme of Requirements part 3 Basic Requirements.

Appendix A: Certificate Profile

Profile of services authenticity and confidentiality certificates for the Private Services domain

Criteria

When defining the fields and attributes within a certificate, the following codes are used:

- V : Compulsory; indicates that the attribute is compulsory and **MUST** be used in the certificate.
- O : Optional; indicates that the attribute is optional and **MAY** be used in the certificate.
- A : Advised against; indicates that the attribute is advised against and **SHOULD NOT** be used in the certificate.
- N: Is **NOT ALLOWED**.

It is not allowed to use fields that are not specified in the certificate profiles.

For the extensions, fields/attributes are used that, in accordance with international standards, are critical, are marked in the 'Critical' column with 'yes' to show that the relevant attribute **MUST** be checked using a process by means of which a certificate is evaluated. Other fields/attributes are shown with 'no'.

Services certificates for authenticity and confidentiality - Private Services domain

Basic attributes

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Version	V	MUST be set at 2 (X.509v3).	RFC 5280	Integer	Describes the version of the certificate, the value 2 stands for X.509 version 3.
SerialNumber	V	A serial number that MUST uniquely identify the certificate within the publishing CA domain.	RFC 5280	Integer	All end user certificates have to contain at least 8 bytes of unpredictable random data in the certificate's serial number (SerialNumber).
Signature	V	MUST be created on the algorithm, as stipulated by the PA.	RFC 5280, ETSI TS 102176	OID	This certificate MUST at least contain a 2048 bit RSA key.
Issuer	V	MUST contain a Distinguished Name (DN). The field contains the following attributes:	PKIo, RFC3739, ETSI TS 102280		Attributes other than those mentioned below MUST NOT be used.
Issuer.countryName	V	See requirement 7.1-pkio174	ETSI TS101862, X520, ISO 3166	Printable String	
Issuer.OrganizationName	V	See requirement 7.1-pkio174	ETSI TS 102280	UTF8String	
Issuer.organizationalUnitName	O	See requirement 7.1-pkio174	ETSI TS 102280	UTF8String	

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Issuer.serialNumber	O	See requirement 7.1-pkio174	RFC 3739	Printable String	
Issuer.commonName	V	See requirement 7.1-pkio174	PKIo, RFC 3739	UTF8String	The commonName attribute MUST NOT be needed to identify the issuing government body (no part of the Distinguished Name, requirement from RFC 3739)
Issuer.organizationIdentifier	V/N	The organizationIdentifier field contains an identification of the issuing CA. This field MUST be present when the subject.organizationIdentifier field is present in the TSP certificate and MUST NOT be present when this field is not part of the corresponding TSP certificate.	EN 319 412-1	String	The syntax of the identification string is specified in paragraph 5.1.4 van ETSI EN 319 412-1 and contains: <ul style="list-style-type: none"> • 3 character legal person identity type reference; • 2 character ISO 3166 [2] country code; • hyphen-minus "-" (0x2D (ASCII), U+002D (UTF-8)); and • identifier (according to country and identity type reference).
Validity	V	MUST define the period of validity of the certificate according to RFC 5280.	RFC 5280	UTCTime	MUST include the start and end date for validity of the certificate in accordance with the applicable policy laid down in the CPS.
Subject	V	The attributes that are used to describe the subject (service) MUST mention the subject in a unique way and include information about the subscriber organization. The field has the following attributes:	PKIo, RFC3739, ETSI TS 102 280		MUST contain a Distinguished Name (DN). Attributes other than those mentioned below MUST NOT be used.
Subject.countryName	V	complete C with two-letter country code in accordance with ISO 3166-1. If an official alpha-2 code is missing, the TSP MAY use the user-assigned code XX.	RFC 3739, X520, ISO 3166, PKIo	PrintableString	The country code that is used in Subject.countryName MUST correspond with the subscriber's address in accordance with the accepted document or registry.

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Subject.commonName	V	Name that identifies the service. In services certificates this field is compulsory	RFC 3739, ETSI TS 102 280, PKIo	UTF8String	Incorporated in the subject.commonname is the function of an organizational entity or the name by which the service, device or system is known. This MAY be a local domain name or host name.
Subject.organizationName	V	The full name of the subscriber's organization in accordance with the accepted document or Basic Registry.	PKIo	UTF8String	The subscriber organization is the organization with which the TSP has entered into an agreement and on behalf of which the certificate holder (service/server) communicates or acts.
Subject.organizationIdentifier	V	The value of the subject:organizationIdentifier field SHALL contain EITHER: <ul style="list-style-type: none"> an identifier conforming to the semantics for legal person identifiers set forth in Section 5.1.4 of ETSI standard EN 319 412-1, or an OIN/HRN number. 	EN 319 412-1	String	TSPs wanting to use a register for legal person identifiers which could qualify as a "national scheme" as described in ETSI standard EN 319 412-1 Section 5.1.4 can apply at Logius for a two-character encoding identifying the relevant source. These encodings will be added to the PKIo CPS. OIN/HRN identifiers adhering to the "national scheme" clause in Section 5.1.4 of ETSI standard EN 319 412-1 are preferred from a standards perspective. This will however mean many governmental systems have to be altered, making this not a likely scenario for the foreseeable future.
Subject.stateOrProvinceName	A	The use is advised against. If present, this field MUST contain the province in which the subscriber is established in accordance with an accepted document or Basic registry.	PKIo, RFC 3739	UTF8String	Name of the province MUST correspond with the address of the subscriber in accordance with the accepted document or registry.
Subject.localityName	A	The use is advised against. If present, this field MUST contain the location of the subscriber in accordance with an accepted document or Basic registry.	PKIo, RFC 3739	UTF8String	Name of the location MUST correspond with the address of the subscriber in accordance with the accepted document or registry.

Field / Attribute	Criteria	Description	Standard reference	Type	Explanation
Subject.serialNumber	O	The TSP is responsible for safeguarding the uniqueness of the subject (service). The Subject.serialNumber MUST be used to identify the subject uniquely. The use of 20 positions is only allowed for OIN and HRN after additional arrangements with Logius.	RFC 3739, X 520, PKIo	Printable String	The number is determined by the TSP and/or the government. The number can differ for each domain and can be used for several applications.
subjectPublicKeyInfo	V	Contains, among other things, the public key.	ETSI TS 102 280, RFC 3279		Contains the public key, identifies the algorithm with which the key can be used.

Standard extensions

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
authorityKeyIdentifier	V	No	The algorithm to generate the AuthorityKey MUST be created on an algorithm determined by the PA.	ETSI TS 102 280, RFC 5280	BitString	The value MUST contain the SHA-1 hash from the authorityKey (public key of the TSP/CA).
SubjectKeyIdentifier	V	No	The algorithm to generate the subjectKey MUST be created on an algorithm determined by the PA.	RFC 5280	BitString	The value MUST contain the SHA-1 hash from the subjectKey (public key of the certificate holder).
KeyUsage	V	Yes	<p>The attribute extension specifies the intended purpose of the key incorporated in the certificate. In the PKI for the government, for each certificate type various bits are incorporated in the keyUsage extension.</p> <p>In authenticity certificates the digitalSignature bit MUST be incorporated and marked as being essential. Another keyUsage MUST NOT be combined with this.</p> <p>In confidentiality certificates, keyEncipherment and dataEncipherment bits MUST be incorporated and marked as being essential. Another keyUsage MUST NOT be combined with this.</p>	RFC 3739, RFC 5280, ETSI TS 102 280	BitString	

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
CertificatePolicies	V	No	<p>MUST contain the OID of the Certificate Policy (CP) and the URI of the Certification Practice Statement (CPS), and MAY contain a user notice. The TSP SHOULD use UTF8String in the userNotice field, but MAY use IA5String.</p> <p>ALL certificates issued with their private key residing on an SSCD (qualified or not) SHOULD contain the ETSI NCP+ OID [0.4.0.2042.1.2]; those issued with their private key NOT residing on an SSCD (qualified or not) SHOULD contain the ETSI NCP OID [0.4.0.2042.1.1].</p> <p>Certificates issued as EU qualified certificates to natural persons with their private key residing in a QSCD, SHOULD contain an additional ETSI QCP-I-qscd OID [0.4.0.194112.1.3], or an additional ETSI QCP-I OID of [0.4.0.194112.1.1] when their private key does not reside on a QSCD.</p>	RFC 3739	OID, String, UTF8String or IA5String	<p>An overview of all Certificate Policy OIDs can be found in the document "PKIoverheid registered OIDs".</p> <p>In the Private Services domain the OIDs for Authenticity and Confidentiality certificates are:</p> <ul style="list-style-type: none"> • Authenticity: 2.16.528.1.1003.1.2.8.4 • Confidentiality: 2.16.528.1.1003.1.2.8.5 <p>Reference to the paragraph numbers of the PoR in the user notice is advised against because the persistency of this cannot be guaranteed (unlike the OID number of the CP).</p>
SubjectAltName	V	No	<p>MUST be used and given a worldwide unique number that identifies the service.</p>	RFC 4043, RFC 5280, PKIo, ETSI 102 280		<p>MUST include a unique identifier in the othername attribute for services certificates. Attributes other than those mentioned below MUST NOT be used.</p>

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
SubjectAltName.otherName	O		<p>MAY contain an extensions:subjectAltName extension with one or more otherName attributes in its extValue field.</p> <p>An otherName attribute is an object consisting out of a sequence of a type-id field and a value field. Each otherName attribute SHALL contain a value to uniquely identify the subject for which the other permitted subject attributes do not qualify.</p> <p>The type-id field of an otherName attribute SHALL contain one of the following OIDs:</p> <ul style="list-style-type: none"> • <i>Microsoft User Principal Name</i> (MSUPN) [1.3.6.1.4.1.311.20.2.3], or • <i>IA5String</i> [1.3.6.1.4.1.1466.115.121.1.26] but MAY also be [2.5.5.5], or • <i>Permanent Identifier</i> [1.3.6.1.5.5.7.8.3] (described in RFC 4043), or • <i>PKIo-arc OID</i> which can be specifically assigned by the PKIo PA for this purpose (should be described in the PKIo-arc OID document). <p>The value field related to otherName attribute type <i>Microsoft User Principal Name</i> (MSUPN):</p> <ol style="list-style-type: none"> 1. SHALL be encoded in UTF8, and 	PKIo	See description.	Normally, otherName attribute type <i>Microsoft User Principal Name</i> (MSUPN) is used for <i>Single Sign-On</i> (SSO) purposes.

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
			<p>2. SHALL use syntax '<code><Subscriber number>@<TSP OID></code>'.</p> <p>The value field related to otherName attribute <i>IA5String</i>:</p> <ol style="list-style-type: none"> 1. SHALL be encoded in ISO 646 (IA5), and 2. SHALL use syntax '<code><TSP OID>-<Subscriber number></code>'. <p>The value field related to otherName attribute <i>Permanent Identifier</i> contains a <i>PermanentIdentifier</i> object, consisting out of a sequence of an <i>identifierValue</i> and an <i>assigner</i> field.</p> <p>The <i>PermanentIdentifier:identifierValue</i> field:</p> <ol style="list-style-type: none"> 1. SHALL be encoded in UTF8, and 2. SHALL use syntax '<code><Subscriber number></code>'. <p>The <i>PermanentIdentifier:assigner</i> field SHALL contain OID '<code><TSP OID></code>'.</p> <p>The value field related to otherName attribute <i>PKIo-arc OID</i> is described in the PKIo-arc OID document.</p> <p>The <code><TSP OID></code> consists out of an OID arc number which:</p> <ul style="list-style-type: none"> • has been assigned to the TSP by the PKIo PA specifically for this usage, expanded by a number chosen by the TSP to specify its identification mechanism, and • is documented in the TSP CPS, and 			

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
			<ul style="list-style-type: none"> is persistent. The <Subscriber number> consists out of a number which: <ul style="list-style-type: none"> uniquely and permanently identifies the subject within the namespace of the corresponding OID, and numbering and/or validation mechanism is described in the TSP CPS. 			
SubjectAltName.rfc822Name	A		MAY be used for the service's e-mail address, for applications that need the e-mail address in order to be able to function properly.	RFC 5280	IA5String	For PKIOverheid certificates, the use of e-mail addresses is advised against, because e-mail addresses of certificate holders often change and are susceptible to spam.
BasicConstraints	O	Yes	This field SHALL have its cA sub-field set to its DEFAULT value (FALSE) resulting in an encoded certificate NOT including the cA sub-field. The optional pathLenConstraint sub-field SHALL NOT be included.	RFC 5280		ITU-T Recommendation X.690 (07/2002) on ASN.1 encoding rules states in Section 5.8: "The encoding of a set value or sequence value shall not include an encoding for any component value which is equal to its default value". Stating in the description that "encoded certificates do NOT include the cA sub-field" therefore is redundant. However, in the past some TSPs employed CA-issuing software which did not do proper ASN.1 encoding resulting in a wrongfully included cA sub-field in encoded certificates. This encoding error resulted in some PKIX software rejecting these certificates. This redundant information therefore has to be regarded as a cautionary hint for TSPs to check their actual certificate encoding for these errors. Chances of this encoding bug still existing in ASN.1 encoding software are however slim since the last mention of such a bug on BugZilla is from 2016.

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
CRLDistributionPoints	V	No	MUST include the URI of a CRL distribution point.	RFC 5280, ETSI TS 102 280		The reference MUST be accessible through the http or LDAP protocol. The attribute Reason MUST NOT be used, reference MUST be made to 1 CRL for all types of reasons for revocation. In addition to CRL, other types of certificate status information service MAY be supported.
ExtKeyUsage	V	No		RFC 5280	KeyPurposeId's	See requirement 7.1-pkio150.

Private extensions

Field / Attribute	Criteria	Critical?	Description	Standard reference	Type	Explanation
authorityInfoAccess	O	No	This attribute MUST include the URI of an OCSP responder if Online Certificate Status Protocol (OCSP) plays a role.			This field can optionally be used to reference other additional information about the TSP.